



Corpo isolante Grigio	<i>Insulating body Grey</i>	Corps isolant Gris	<i>Isolierkörper Grau</i>	PA68 UL94VO
Vite	<i>Screw</i>	Vis	<i>Schraube</i>	M2,5-CB15+Zn
Morsetto	<i>Clamp</i>	Borne	<i>Klemmkörper</i>	C60+Zn
Contatto	<i>Pin</i>	Contacte	<i>Kontakt</i>	CuZn37+Ni+Sn
Coppia di torsione	<i>Testing torque</i>	Couple de serrage	<i>Zul. Drehmoment</i>	0,4 Nm
Sezione	<i>Section</i>	Section	<i>Querschnitt</i>	1,5 mm ²
Foro di montaggio	<i>P.C.B. mounting hole</i>	Perçage C. I.	<i>Leiterplattenbohrung</i>	Ø 1,3 mm
Corrente nominale	<i>Nominal current</i>	Courant nominal	<i>Strombelastbarkeit</i>	17,5 A
Tensione	<i>Voltage</i>	Tension	<i>Betriebsspannung</i>	130/750 V
Temperatura	<i>Temperature</i>	Température	<i>Temperatur</i>	85°C
Grado di protezione	<i>Protection index</i>	Degré de protection	<i>Schutzklasse</i>	IP00
Resistenza di isolamento	<i>Insulation resistance</i>	Résistance d'isolement	<i>Isolationswiderstand</i>	≥ 5 MΩ
Rigidità dielettrica	<i>Dielectric strength</i>	Rigidité diélectrique	<i>Durchschlagsfestigkeit</i>	≥ 1250 Vac/60"



